

## Generative recursion

**Readings:** Sections 25, 26, 27, 30, 31

**Topics:**

- What is generative recursion?
- Termination
- Hoare's Quicksort
- Modifying the design recipe
- Example: breaking strings into lines

Intro ○○○ 1/28	Termination ○○○○	Quicksort ○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○ CS 135
----------------------	---------------------	-------------------------------------------------	--------------	---------------------------------

## What is generative recursion?

Simple and accumulative recursion, which we have been using so far, is a way of deriving code whose form parallels a data definition.

**Generative recursion** is more general: the recursive cases are **generated** based on the problem to be solved.

The non-recursive cases also do not follow from a data definition.

It is much harder to come up with such solutions to problems.

It often requires deeper analysis and domain-specific knowledge.

Intro ●○○ 2/28	Termination ○○○○	Quicksort ○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○ CS 135
----------------------	---------------------	-------------------------------------------------	--------------	---------------------------------

## > Example revisited: GCD

```
;; (euclid-gcd n m) computes gcd(n,m) using Euclidean algorithm
;; euclid-gcd: Nat Nat → Nat
(define (euclid-gcd n m)
  (cond [(zero? m) n]
        [else (euclid-gcd m (remainder n m))]))
```

Intro ●○○ 3/28	Termination ○○○○	Quicksort ○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○ CS 135
----------------------	---------------------	-------------------------------------------------	--------------	---------------------------------

## > Why does this work?

**Correctness:** Follows from Math 135 proof of the identity.

**Termination:** An application **terminates** if it can be reduced to a value in finite time.

All of our functions so far have terminated. But why?

For a non-recursive function, it is easy to argue that it terminates, assuming all applications inside it do.

It is not clear what to do for recursive functions.

Intro ○○● 4/28	Termination ○○○○○	Quicksort ○○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○○ CS 135
----------------------	----------------------	--------------------------------------------------	--------------	----------------------------------

## Termination of recursive functions

Why did our functions using simple recursion terminate?

A simple recursive function always makes recursive applications on smaller instances, whose size is bounded below by the base case (e.g. the empty list).

We can thus bound the **depth of recursion** (the number of applications of the function before arriving at a base case).

As a result, the evaluation cannot go on forever.

Intro ○○○ 5/28	Termination ●○○○○	Quicksort ○○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○○ CS 135
----------------------	----------------------	--------------------------------------------------	--------------	----------------------------------

## > Depth of recursion example

```
(define (sum-list lst)
  (cond [(empty? lst) 0]
        [else (+ (first lst) (sum-list (rest lst)))]))
```

```
(sum-list (list 3 6 5 4))           ;; 1
⇒ (+ 3 (sum-list (list 6 5 4)))    ;; 2
⇒ (+ 3 (+ 6 (sum-list (list 5 4)))) ;; 3
⇒ (+ 3 (+ 6 (+ 5 (sum-list (list 4))))) ;; 4
⇒ (+ 3 (+ 6 (+ 5 (+ 4 (sum-list (list )))))) ;; arrived at base case
⇒ (+ 3 (+ 6 (+ 5 (+ 4 0)))) ⇒ ... ⇒ 18
```

The depth of recursion of any application of `sum-list` is equal to the length of the list to which it is applied.

For generatively recursive functions, we need to make a similar argument.

Intro ○○○ 6/28	Termination ●○○○○	Quicksort ○○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○○ CS 135
----------------------	----------------------	--------------------------------------------------	--------------	----------------------------------

## > Termination of `euclid-gcd`

In the case of `euclid-gcd`, our measure of progress is the size of the second argument.

If the first argument is smaller than the second argument, the first recursive application switches them, which makes the second argument smaller.

After that, the second argument always gets smaller in the recursive application (since  $m > n \bmod m$ ), but it is bounded below by 0.

Thus any application of `euclid-gcd` has a depth of recursion bounded by the second argument.

In fact, it is always much faster than this.

Intro  
○○○  
7/28

Termination  
○○○○○

Quicksort  
○○○○○○○  
15: Generative Recursion


DRecipe  
○

Example  
○○○○○○○○○○○  
CS 135

## > Termination is sometimes hard

```
;; collatz: Nat → Nat
(define (collatz n)
  (cond
    [(= n 1) 1]
    [(even? n) (collatz (/ n 2))]
    [else (collatz (+ 1 (* 3 n)))]))
```

It is a decades-old open research problem to discover whether or not `(collatz n)` terminates for all values of `n`.



THE COLLATZ CONJECTURE STATES THAT IF YOU PICK A NUMBER, AND IF IT'S EVEN DIVIDE IT BY TWO AND IF IT'S ODD MULTIPLY IT BY THREE AND ADD ONE, AND YOU REPEAT THIS PROCEDURE LONG ENOUGH, EVENTUALLY YOUR FRIENDS WILL STOP CALLING TO SEE IF YOU WANT TO HANG OUT.  
<https://xkcd.com/718/>

Intro  
○○○  
8/28

Termination  
○○○○○

Quicksort  
○○○○○○○  
15: Generative Recursion

DRecipe  
○

Example  
○○○○○○○○○○○  
CS 135

## > `collatz-list`

We can see better what `collatz` is doing by producing a list.

```
;; (collatz-list n) produces the list of the intermediate
;; results calculated by the collatz function.
;; collatz-list: Nat → (listof Nat)
;; requires: n >= 1
(check-expect (collatz-list 1) '(1))
(check-expect (collatz-list 5) '(5 16 8 4 2 1))

(define (collatz-list n)
  (cons n (cond
    [(= n 1) empty]
    [(even? n) (collatz-list (/ n 2))]
    [else (collatz-list (+ 1 (* 3 n)))])))
```

Intro  
○○○  
9/28

Termination  
○○○○○

Quicksort  
○○○○○○○  
15: Generative Recursion

DRecipe  
○

Example  
○○○○○○○○○○○  
CS 135

## Hoare's Quicksort

The Quicksort algorithm is an example of **divide and conquer**:

- divide a problem into smaller subproblems;
- recursively solve each one;
- combine the solutions to solve the original problem.

Quicksort sorts a list of numbers into non-decreasing order by first choosing a **pivot** element from the list.

The subproblems consist of the elements less than the pivot, and those greater than the pivot.

Intro ○○○ 10/28	Termination ○○○○○	Quicksort ●○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○ CS 135
-----------------------	----------------------	-------------------------------------------------	--------------	---------------------------------

### > Quicksort example

If the list is (`list 9 4 15 2 12 20`), and the pivot is 9, then the subproblems are (`list 4 2`) and (`list 15 12 20`).

Recursively sorting the two subproblem lists gives (`list 2 4`) and (`list 12 15 20`).

It is now simple to combine them with the pivot to give the answer.

(`append (list 2 4) (list 9) (list 12 15 20)`)  $\Rightarrow$  '(2 4 9 12 15 20)

Intro ○○○ 11/28	Termination ○○○○○	Quicksort ●○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○ CS 135
-----------------------	----------------------	-------------------------------------------------	--------------	---------------------------------

### > Pivot and subproblems

The easiest pivot to select from a list `lon` is (`first lon`).

A function which tests whether another item is less than the pivot is (`lambda (x) (< x (first lon))`).

The first subproblem is then (`filter (lambda (x) (< x (first lon))) lon`)

A similar expression will find the second subproblem (items greater than the pivot).

Intro ○○○ 12/28	Termination ○○○○○	Quicksort ●○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○ CS 135
-----------------------	----------------------	-------------------------------------------------	--------------	---------------------------------

## > my-quicksort

```
;; (my-quicksort lon) sorts lon in non-decreasing order
;; my-quicksort: (listof Num) → (listof Num)
(define (my-quicksort lon)
  (cond [(empty? lon) empty]
        [else (local [(define pivot (first lon))
                       (define less (filter (lambda (x) (< x pivot))
                                             (rest lon)))
                       (define greater (filter (lambda (x) (>= x pivot))
                                               (rest lon)))]
              (append (my-quicksort less)
                      (list pivot) (my-quicksort greater)))]))

(check-expect (my-quicksort '(5 3 9)) '(3 5 9))
```

Intro  
○○○  
13/28

Termination  
○○○○

Quicksort  
○○●○○○  
15: Generative Recursion

DRecipe  
○

Example  
○○○○○○○○○○  
CS 135

## > Quicksort termination

Termination of quicksort follows from the fact that both subproblems have fewer elements than the original list (since neither contains the pivot).

Thus the depth of recursion of an application of `my-quicksort` is bounded above by the number of elements in the argument list.

This would not have been true if we had mistakenly written  
`(filter (lambda (x) (>= x pivot)) lon)` instead of the correct  
`(filter (lambda (x) (>= x pivot)) (rest lon))`.

Intro  
○○○  
14/28

Termination  
○○○○

Quicksort  
○○●○○○  
15: Generative Recursion

DRecipe  
○

Example  
○○○○○○○○○○  
CS 135

## > Built-in quicksort

In the teaching languages, the built-in function `quicksort` consumes two arguments, a list and a comparison function.

```
(quicksort '(1 5 2 4 3) <) ⇒ '(1 2 3 4 5)
(quicksort '(1 5 2 4 3) >) ⇒ '(5 4 3 2 1)

(quicksort '("chili powder" "anise" "bazil") string<?)
⇒ (list "anise" "bazil" "chili powder")
```

Intro  
○○○  
15/28

Termination  
○○○○

Quicksort  
○○●○○○  
15: Generative Recursion

DRecipe  
○

Example  
○○○○○○○○○○  
CS 135

## > Degenerative quicksort

Intuitively, quicksort works best when the two recursive function applications are on arguments about the same size.

When one recursive function application is always on an empty list (as is the case when `quicksort` is applied to an already-sorted list), the pattern of recursion is similar to the worst case of insertion sort, and the number of steps is roughly proportional to the square of the length of the list.

We will go into more detail on efficiency considerations in CS 136.

Intro ○○○ 16/28	Termination ○○○○○	Quicksort ○○○○○○● 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○○○○ CS 135
-----------------------	----------------------	--------------------------------------------------	--------------	----------------------------------

## Modifying the design recipe

The design recipe becomes much more vague when we move away from data-directed design.

The purpose statement remains unchanged, but additional documentation is often required to describe **how** the function works.

Examples need to illustrate the workings of the algorithm.

We cannot apply a template, since there is no data definition.

For divide and conquer algorithms, there are typically tests for the easy cases that don't require recursion, followed by the formulation and recursive solution of subproblems, and then combination of the solutions.

Intro ○○○ 17/28	Termination ○○○○○	Quicksort ○○○○○○○ 15: Generative Recursion	DRecipe ●	Example ○○○○○○○○○○○ CS 135
-----------------------	----------------------	--------------------------------------------------	--------------	----------------------------------

## Example: breaking strings into lines

Traditionally, the character set used in computers has included not only alphanumeric characters and punctuation, but "control" characters as well.

An example in Racket is `#\newline`, which signals the start of a new line of text. The characters `'\'` and `'n'` appearing consecutively in a string constant are interpreted as a single newline character.

For example, the string `"ab\n cd"` is a five-character string with a newline as the third character. It would typically be printed as `"ab"` on one line and `"cd"` on the next line.

Intro ○○○ 18/28	Termination ○○○○○	Quicksort ○○○○○○○ 15: Generative Recursion	DRecipe ○	Example ●○○○○○○○○○ CS 135
-----------------------	----------------------	--------------------------------------------------	--------------	---------------------------------

## > Getting started

Consider converting a string such as "one\ntwo\nthree" into a list of strings, (list "one" "two" "three"), one for each line.

The solution will start with an application of `string→list`. That's the only way we've studied of working with individual characters in a string.

This problem can be solved using simple recursion on the resulting list of characters – but it's hard. The "simple" recursion gets bogged down in a lot of little details.

In this case a generative solution is easier.

Intro ○○○ 19/28	Termination ○○○○	Quicksort ○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○●○○○○○○○ CS 135
-----------------------	---------------------	-------------------------------------------------	--------------	---------------------------------

## > The generative idea

Instead of thinking of the list of characters as a list of characters, think of it as a list of lines:

o n e \n t w o \n t h r e e

o n e \n t w o \n t h r e e

A list of lines is either empty or a line followed by a list of lines.

Start with helper functions that divide the list of characters into the first line and the rest of the lines.

Intro ○○○ 20/28	Termination ○○○○	Quicksort ○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○●○○○○○○○ CS 135
-----------------------	---------------------	-------------------------------------------------	--------------	---------------------------------

## > Helper: first-line

```
;; (first-line loc) produces longest newline-free prefix of loc  
;; first-line: (listof Char) → (listof Char)
```

```
(define (first-line loc)  
  (cond [(empty? loc) empty]  
        [(char=? (first loc) #\newline) empty]  
        [else (cons (first loc) (first-line (rest loc)))]))
```

```
(check-expect (first-line empty) empty)  
(check-expect (first-line '(#\a #\newline)) '(#\a))  
(check-expect (first-line (string→list "abc\ndef")) '(#\a #\b #\c))
```

Intro ○○○ 21/28	Termination ○○○○	Quicksort ○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○●○○○○○○○ CS 135
-----------------------	---------------------	-------------------------------------------------	--------------	---------------------------------

## > Helper: rest-of-lines

```
;; (rest-of-lines loc) produces loc with everything up to
;; and including the first newline removed
;; rest-of-lines: (listof Char) → (listof Char)

(define (rest-of-lines loc)
  (cond [(empty? loc) empty]
        [(char=? (first loc) #\newline) (rest loc)]
        [else (rest-of-lines (rest loc))]))

(check-expect (rest-of-lines empty) empty)
(check-expect (rest-of-lines '#\a #\newline)) empty)
(check-expect (rest-of-lines '#\a #\newline #\b)) '#\b))
```

Intro  
○○○  
22/28

Termination  
○○○○○

Quicksort  
○○○○○○○  
15: Generative Recursion

DRecipe  
○

Example  
○○○○●○○○○○  
CS 135

## > List of lines template

We can create a “list of lines template” using these helpers.

```
(define (loc→lol loc)
  (local [(define fline (first-line loc))
          (define rlines (rest-of-lines loc))])
  (cond [(empty? loc) empty]
        [else ... fline ... (loc→lol rlines) ...]))
```

This looks a lot like the template for functions consuming a `(listof X)`. That was simple recursion.

This is **not** simple recursion. Why not?

Intro  
○○○  
23/28

Termination  
○○○○○

Quicksort  
○○○○○○○  
15: Generative Recursion

DRecipe  
○

Example  
○○○○●○○○○○  
CS 135

## > loc→lol

```
;; loc→lol: (listof Char) → (listof Str)
(check-expect (loc→lol (string→list "abc\ndef"))) (list "abc" "def"))
(check-expect (loc→lol (string→list "")) (list))
(check-expect (loc→lol (string→list "\ndef"))) (list "" "def"))

(define (loc→lol loc)
  (local [(define fline (first-line loc))
          (define rlines (rest-of-lines loc))])
  (cond [(empty? loc) empty]
        [else (cons (list→string fline)
                      (loc→lol rlines))]))
```

Intro  
○○○  
24/28

Termination  
○○○○○

Quicksort  
○○○○○○○  
15: Generative Recursion

DRecipe  
○

Example  
○○○○●○○○○○  
CS 135



## > Generative recursion (1/2)

Why is this generative recursion?

`loc→lol` can be rewritten as

```
(define (loc→lol loc)
  (cond [(empty? loc) empty]
        [else (cons (list→string (first-line loc))
                     (loc→lol (rest-of-lines loc)))]))
```

The recursive call to `loc→lol` is *not* using the data definition for a list of characters. It often gets many steps closer to the base case in one recursive application.

Intro ○○○ 25/28	Termination ○○○○	Quicksort ○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○●○○ CS 135
-----------------------	---------------------	-------------------------------------------------	--------------	----------------------------------

## > Generative recursion (2/2)

It *is* using a data definition of a “list of lines”, but that’s a higher-level abstraction that we imposed on top of the `(listof Char)`, our actual argument.

The key part of the generative recursion pattern is that the argument to `loc→lol` is being generated by `rest-of-lines`.

With generative recursion we needed that “aha” that transformed the problem into a list of lines. That “aha” is often difficult to see.

Was it worth it? Consider the solution using “simple” recursion on the next slide.

Intro ○○○ 26/28	Termination ○○○○	Quicksort ○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○●○○ CS 135
-----------------------	---------------------	-------------------------------------------------	--------------	----------------------------------

## > Using simple recursion

```
(define (list→lines loc)
  (cond
    [(empty? loc) (list empty)]
    [(and (empty? (rest loc)) (char=? #\newline (first loc)))
     (list empty)]
    [else
     (local [(define r (list→lines (rest loc)))]
       (cond
         [(char=? #\newline (first loc)) (cons empty r)]
         [else (cons (cons (first loc) (first r)) (rest r))]))]))

;; string→strlines: string → (listof string)
;; converts string to list of lines (strings) based on newlines
(define (string→strlines str)
  (map list→string (list→lines (string→list str))))
```

Intro ○○○ 27/28	Termination ○○○○	Quicksort ○○○○○○ 15: Generative Recursion	DRecipe ○	Example ○○○○○○○○●○○ CS 135
-----------------------	---------------------	-------------------------------------------------	--------------	----------------------------------

## Goals of this module

- You should understand the idea of generative recursion, why termination is not assured, and how a quantitative notion of a measure of progress towards a solution can be used to justify that such a function will return a result.
- You should understand the examples given.

Intro  
○○○  
28/28

Termination  
○○○○○

Quicksort  
○○○○○○○  
15: Generative Recursion

DRecipe  
○

Example  
○○○○○○○○○●  
CS 135