Review: MIPS Register Usage

```
R0,  $0  = ## zero
R2,  $2  = ## return value / system call number
R4,  $4  = ## 1st argument
R5,  $5  = ## 2nd argument
R6,  $6  = ## 3rd argument
R7,  $7  = ## 4th argument
R29, $29 = ## stack pointer
R30, $30 = ## frame pointer
R31, $31 = ## return addr
```


How a System Call Works

```
/* In Nachos all user programs are linked
 * with start.s, it begins at virtual address 0
 */
  .globl __start
  .ent    __start
__start:
  jal     main  ## store addr of next
  move    $4,$0 ##   instr in $31 then jump
  jal     Exit  ## if return from main exit(0)
  .end __start
```

How a System Call Works

```
/* call.c
 * Show how a function/syscall is made.
 */
#include "syscall.h"

int
main()
{
  ## Q: What's wrong with this code?
  ## A: It isn't checking the return code
  Write("Hello World\n", 12, 1);
}
```


How a System Call Works

```
  .file   1 "call.c"
  .rdata    ## read only data segment
  .align  2  ## to 1=byte 2=word 3=dw
$LC0:
  .ascii  "Hello World\n\000"
  .text     ## start text/code segment
  .align  2
  .globl  main
  .ent  main
```

How a System Call Works

```
main:
  .frame  $fp,24,$31
  .mask  0xc0000000,-4 ## bitmask saved regs
  .fmask  0x00000000,0 ## saved fp regs
  subu  $sp,$sp,24     ## min frame size 24
  sw  $31,20($sp)      ## save ret addr
  sw  $fp,16($sp)      ## save old frame ptr
  move  $fp,$sp        ## setup new frame ptr
  jal  __main          ## for system init
  la  $4,$LC0          ## addr of string arg1
  li  $5,0x0000000c    ## 12             arg2
  li  $6,0x00000001    ## 1              arg3
  jal  Write           ## call Write
```


How a System Call Works

```
$L1:
  .set  noreorder
  move  $sp,$fp      ## set stack ptr
  lw  $31,20($sp)    ## restore ret addr
  lw  $fp,16($sp)    ## restore frame ptr
  j  $31             ## return to __start
  addu  $sp,$sp,24   ## branch delay slot!
  .set  reorder      ##  pops stack frame
  .end  main
```

How a System Call Works

```
/* dummy function to keep gcc happy */
        .globl  __main
        .ent    __main
__main:
        j       $31     ## return to point of call
        .end    __main ## i.e. back to __start
```


How a System Call Works

```
## start.s Comments: System call stubs:
## Assembly language assist to make system
## calls to the Nachos kernel.  There is one
## stub per system call, that places the code
## for the system call into register r2, and
## leaves the arguments to the system call
## alone (in other words, arg1 is in r4, arg2
## is in r5, arg3 is in r6, arg4 is in r7)
##
## The return value is in r2. This follows the
## standard C calling convention on the MIPS.
```

How a System Call Works

```
        .globl Write
        .ent    Write
Write:
        addiu $2,$0,SC_Write
        syscall
        j       $31
        .end Write
```


How a System Call Works

```
/* system call codes */
#define SC_Halt         0
#define SC_Exit         1
#define SC_Exec         2
#define SC_Join         3
#define SC_Create       4
#define SC_Open         5
#define SC_Read         6
#define SC_Write        7
#define SC_Close        8
#define SC_Fork         9
#define SC_Yield        10
```

How a System Call Works

```
void ExceptionHandler(ExceptionType which)
{
  int type = kernel->machine->ReadRegister(2);

  kernel->currentThread->SaveUserState();
  kernel->currentThread->space->SaveState();

  switch(which) {
  case SyscallException:
    switch(type) {

    case SC_Write:
      vaddr = kernel->machine->ReadRegister(4);
      len = kernel->machine->ReadRegister(5);
      fileID = kernel->machine->ReadRegister(6);
      retval = WriteHandler(fileID, vaddr, len);
      break;
```


C Code for Segments Example

```
#define N   (5)   ## Proprocessor replaces this

unsigned int x = 0xdeadbeef;  # initialized data
int y = 0xbb;                 # ditto
const int blah = 0xff;        # rdata (read only)
int data[N];                  # uninit data

struct info {   ## Doesn't use any storage!
  int x;
  int y;
};
```

C Code for Segments Example (cont'd)

```
main()
{
  int i;
  int j = 0xaa;
  int k;
  const int l = 0xee;  ## all above in regs/stack
  char *str = "Hello World\n";
  ## str in on stack or register
  ## Hello World in .rdata

  for (i=0; i<N; i++) {
    data[i] = i;  ## code/instructs in text
  }
}
```


Coff2noff Output for Segments

```
Loading 4 sections:
".text"  filepos  52  (0x34)      mempos    0   (0x0)
         size 736 (0x2e0)
".rdata" filepos 788 (0x314)      mempos  768 (0x300)
         size  32 (0x20)
".data"  filepos 820 (0x334)      mempos  896 (0x380)
         size  16 (0x10)
".bss"   filepos  -1 (0xffffffff) mempos 1024 (0x400)
         size  20 (0x14)
<not in file>
## See next few slides for explanations
```

Coff2noff Output for Segments

```
## .text  at 0x34 (52) in file
##       size = 0x2e0 (736 bytes)
##       starts at to virtual addr 0x0

## .rdata at .text start (52) + text size (736)
##           = 788 in file
##  Contains 4 bytes for int blah and 13 for
##  "Hello World\n\0" total = 17
##  (word aligned in file, page aligned in mem)
##  Page = 128 bytes
##  1 =  0x80, 2 = 0x100, 3 = 0x180, 4 = 0x200,
##  5 = 0x280, 6 = 0x300  7 = 0x380, 8 = 0x400
##  .rdata starts at 0x300 in virtual memory
```


Coff2noff Output for Segments

```
## .data in file at .rdata start (788) +
##       .rdata size (32) = 820
##  Contains 4 bytes for int x + 4 bytes for yy = 8
##  .data starts at 0x380 in virtual memory

## .bss (no where becase no values to store)

## (bss = Block Started by Symbol)
## have only a name / symbol but no value
## (uninitialized data)
```

Some Output from objdump

```
Contents of section .rdata:
0300 ff000000 48656c6c 6f20576f 726c640a
     ....Hello World.
0310 00000000 00000000 00000000 00000000
     ................
Contents of section .data:
0380 efbeadde bb000000 00000000 00000000
     ................
## See next slides for explanation
```


Some Output from objdump

```
## H = 0x48 e = 0x65 l = 6c ... \n = 0x0a

## x = 0xdeadbeef /* 3735928559 */
## Byte ordering.  Mips - little endian
## Least significant byte at lowest address
## Word addressed by address of least sign. byte
#
## 0 .. 7 8.. 15 16..23 24..31
## [ ef ] [ be ] [ ad ] [ de ]

## Big Endian
## Most significant byte at lowest address
## Word addressed by address of most sign. byte

## 0 .. 7 8 ..15 16..23 24..31
## [ de ] [ ad ] [ be ] [ ef ]
```